

PowerPack NC140-1

Nominal output current 140A

Item number 120120



Properties

On-board closed design power supply unit with integrated fan

Area of application: trade shows and exhibitions. The *PowerPack* is installed instead of the vehicle battery, thus ensuring a permanent supply of power to the on-board electrical system during trade shows or exhibitions.

Input voltage range 88...264 VAC, 47 .. 63 Hz
Rated input current 15 A/230 VAC under full load
Inrush current 80 A/230 VAC
Leakage current < 1.0 mA/240 VAC
Efficiency ratio 84%
Housing dimensions in mm approx.: L=315/D: 175/H: 190

Short-circuit protected
Integrated overload protection (current limit)
Integrated surge protection (switch off)
Integrated overtemperature protection (85°C, switch off with continuous operation of fan)

Integrated PFC, factor: 0.95/230 VAC, 0.99/115 VAC under full load

Corresponds with the guidelines
UL 60950-1, C-UL (CSA60950-1)
EN 60950-1, EN 50 178 (DEN-AN), EN 55011-B, EN 55022-B
FCC Teil 15 Klasse B

Operating temperature -20 ... +50 °C
Storage temperature -40 ... +85 °C

Output voltage 10.50 ... 16.50 VDC (internally adjustable)
Rated output current 140A
Output voltage tolerance +- 1%

Sickert & Hafner GmbH

Automotive Systems

Berliner Straße 9

D-63628 Bad Soden-Salmünster

Phone +49 (0) 6056-900-570

Fax +49 (0) 6056-900-5711

Sales@sickert-hafner.de

www.sickert-hafner.de