

# PowerPack NC50

Nominal output current 50A

Item number 120110



## Properties

On-board closed design power supply unit with integrated fan

Area of application: trade shows and exhibitions. The *PowerPack* is installed instead of the vehicle battery, thus ensuring a permanent supply of power to the on-board electrical system during trade shows or exhibitions.

Input voltage range 88...264 VAC, 47 .. 63 Hz  
Rated input current 8.2A/230 VAC under full load  
Inrush current 40A/230 VAC  
Leakage current < 1.3 mA/240 VAC  
Efficiency ratio 84%  
Housing dimensions in mm approx.: L=275/D: 175/H: 177

Short-circuit protected  
Integrated overload protection (current limit)  
Integrated surge protection (switch off)  
Integrated overtemperature protection (85°C, switch off with continuous operation of fan)

Integrated PFC, factor: 0.95/230 VAC, 0.99/115 VAC under full load

Corresponds with the guidelines  
EN55022 (CISPR22) class B  
EN61000-3-2, -3  
EN61000-4-2, 3, 4, 5, 6, 8 ,11; ENV50204 A  
UL 60950-1

Operating temperature -20 ... +50 °C  
Storage temperature -40 ... +85 °C

Output voltage 10 ... 13.2 VDC (internally adjustable)  
Rated output current 50A  
Output voltage tolerance +- 1%

### Sickert & Hafner GmbH

Automotive Systems

Berliner Straße 9

D-63628 Bad Soden-Salmünster

Phone +49 (0) 6056-900-570

Fax +49 (0) 6056-900-5711

[Sales@sickert-hafner.de](mailto:Sales@sickert-hafner.de)

[www.sickert-hafner.de](http://www.sickert-hafner.de)